

API MULTIPURPOSE SMALL SHELTER 20'W x 32'-6"L x 10'H



AVAILABLE FOR IMMEDIATE DELIVERY
OVER 500 INSTOCK



**ALL POINTS INTERNATIONAL DIST. INC., 74 PROSPECT PLACE—HILLSDALE, NJ 07642. PHONE: (201) 573 — 0997
FAX: (201) 391—0632 EMAIL: APIMAIL@API-STRUCTURES.COM WEBSITE: WWW.API-STRUCTURES.COM
WORLDWIDE GSA CONTRACT # GS—07F—9034D**

API Multipurpose Small Shelter Specifications:

Size: 20' wide x 32'-6" long x 10' high (Steel or Aluminum Frame available)
Design Loads: 90 MPH Wind Load (85 MPH Sustained Wind Load) & 30 PSF Snow Load
Fabric: Desert Tan, 18 Oz. PVC Fire rated & High UV rated material
Doors: Front Steel or Aluminum Personnel Door 3' x 7' and fabric zipper door rear which can be upgraded to Steel or Aluminum Personnel Door.
Windows: (14) 30" x 42" screened windows. 2 on front end wall, 2 on rear end wall and 10 on the main cover.
Options:

- Tent Electrical — (6) 100-watt incandescent light fixtures. (1) – 20 amp load center panel with 6 quadruplex outlets (24 total plugs) per side. Plug and play electrical power configured for either 50/60 Hz.
- Vinyl Floor —15 oz. non-slip vinyl floor; 6" lip around perimeter that attaches to the side and end walls to prevent the intrusion of dust, insects and water from entering the shelter.
- Hard Flooring System— non-slip floor covering the complete interior. Slip fit – snap fit design individual 4" x 12" pieces with predrilled holes 4ft apart for anchoring with supplied anchor spikes.
- Tent Vestibules – 7'wide x 8'long x 8'-6"high Vestibule that attaches completely weather tight to the front of the tent.
- ECU (Environmental Control Units) - (1) 5 ton ECU unit per tent. 50/60Hz ECU includes heat and a/c along with fresh air intake and exhaust – 18" interior duct plenum (with elbow section to distribute a/c and heat evenly throughout the shelter) – 22" outside dimension. Interior fabric ducting to distribute air throughout the tent. Thermostat included, ECU unit provides minimum 60,000 BTU cooling and minimum 37,000 BTU heating. Pre-wired no certified electrician required to assemble. ECU ports on both front and rear fabric panels. ECU can be lifted by forklift.
- Interior Air Bladder Liner – Insulates interior of tent. The tent will maintain between 74°F and 77°F at an ambient temp of -10° F thru +100° F.
- Spares/Repair Kit — Complete with glue, window screen material, fabric (both inner & outer), spare bulbs & tent anchors.
- (5) Tent Distribution System – includes (1) 90 kw at prime (actual 110kw) generator, skid mounted, 3 phase prime power. Complete with battery operated starter, internal fuel tank, sound attenuation enclosure. (1) 5 shelter PDS 50 or 60 Hz to distribute power to all 5 tents—plug and play. All distribution boxes CE/UL listed compliant. Breakers are RCD type.
- (10) Tent Distribution System – includes (1) 176 kw at prime (actual 220kw) generator, skid mounted, 3 phase prime power. Complete with battery operated starter, internal fuel tank, sound attenuation enclosure. (1) 10 shelter PDS 50 or 60 Hz to distribute power to all 10 tents—plug and play. All distribution boxes CE/UL listed compliant. Breakers are RCD type.
- Shelters of the same size can be connected together.

*** MANY OTHER STRUCTURE SIZES AVAILABLE WITH SIMILAR OPTIONS ***

**ALL POINTS INTERNATIONAL DIST. INC., 74 PROSPECT PLACE—HILLSDALE, NJ 07642. PHONE: (201) 573 — 0997
FAX: (201) 391—0632 EMAIL: APIMAIL@API-STRUCTURES.COM WEBSITE: WWW.API-STRUCTURES.COM
WORLDWIDE GSA CONTRACT # GS—07F—9034D**